

HIKVISION Camara Mini Domo IP lente fijo 4mm - 4 MP - EXIR- PoE



HIKVISION®

Short Description

2688 × 1520 a 30 fps

- IR: hasta 10 m • H.265, H.265 +
- 120dB WDR
- Ranura Micro SD / SDHC / SDXC incorporada, hasta 128 GB
- PoE
- EXIR

Marca: Hikvision

Código del producto: 2029, DS-2CD2523GO-IS (4MM)

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Descripción

2688 × 1520 a 30 fps

- IR: hasta 10 m • H.265, H.265 +
- 120dB WDR
- Ranura Micro SD / SDHC / SDXC incorporada, hasta 128 GB
- PoE
- EXIR

Camera

Image Sensor:

Signal System:

Min. Illumination:

Shutter time:

Slow shutter:

Lens:

Lens Mount:

Adjustment Range:

Day& Night:

Wide Dynamic Range:

Digital noise reduction:

Focus:

Compression Standard

1/3" Progressive Scan CMOS

PAL/NTSC

Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR

1/3 s to 1/100,000 s

Support

2.8 mm: Horizontal field of view: 98°, Vertical field of view: 55°, Diagonal field of view: 114°

4 mm: Horizontal field of view: 78°, Vertical field of view: 42°, Diagonal field of view: 93°

6 mm: Horizontal field of view: 48°, Vertical field of view: 27°, Diagonal field of view: 54°

M12

Pan: -30° to +30°, tilt: 0° to 75°, rotate: 0° to 360°

IR Cut Filter

120 dB

3D DNR

Fixed

Video Compression:	H.265+/H.265/H.264+/H.264/MJPEG
H.264 code profile:	Main Profile/High Profile
Video bit rate:	256Kbps~16Mbps
Audio Compression:	G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Triple Streams:	Yes
Image	
Max. Image Resolution:	2688 × 1520
Frame Rate:	50Hz: 25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)
Sub Stream:	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream:	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement:	BLC/3D DNR/ROI/HLC
Image Settings:	Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser
ROI:	Support 1 fixed region for main stream and sub-stream separately
Day/Night Switch:	Auto/Schedule/Day/Night/Triggered by Alarm In (-S model)
Network	
Network Storage:	microSD/SDHC/SDXC card

(128G), local storage and
NAS (NFS,SMB/CIFS),
ANR

Alarm Trigger:

Motion detection, video
tampering alarm, network
disconnected, IP address
conflict, illegal login, HDD
full, HDD error

Protocols:

TCP/IP, UDP, ICMP, HTTP,
HTTPS, FTP, DHCP, DNS,
DDNS, RTP, RTSP, RTCP,
PPPoE, NTP, UPnP, SMTP,
SNMP, IGMP, 802.1X, QoS,
IPv6

General Function:

One-key reset, Anti-Flicker,
heartbeat, mirror, password
protection, privacy
mask, Watermark, IP address
filtering

System Compatibility:

ONVIF (Profile S, Profile G),
ISAPI

Interface

Audio:

with -S model?2 Inputs: line
in or mic in (built-in
microphone), 1 output: line
out, mono sound, terminal
block

Communication Interface:

1 RJ45 10M / 100M Ethernet
interface

Alarm:

with -S model?1 Input:
Alarm in, 1 Output: Alarm
out (max. 12 VDC, 30 mA),
terminal block

On-board storage:

Built-in Micro
SD/SDHC/SDXC slot, up to
128 GB

Reset Button:

Yes

Audio

Environment Noise Filtering:

Support

Audio Sampling Rate:

8 kHz/16 kHz/32 kHz/44.1

kHZ/48 kHz

Smart Feature-set
Behavior Analysis:

Line crossing detection,
intrusion detection

Line Crossing Detection:

Cross a pre-defined virtual
line

Intrusion Detection:

Enter and loiter in a pre-
defined virtual region

Recognition:

Face Detection

Wi-Fi Specification (-W)

Wireless Standards:

IEEE802.11b, 802.11g,
802.11n

Frequency Range:

2.412 GHz to 2.4835 GHz

Channel Bandwidth:

20/40MHz Support

Security:

WPA, WPA2

Transmission Rate:

11b: 11Mbps

11g: 54Mbps

11n: up to 150Mbps

Wireless Range:

50m(depend on environment)

Protocols:

802.11b: DQPSK, DBPSK,
CCK

802.11g/n: OFDM

/64-QAM,16-QAM, QPSK,
BPSK

General

Operating Conditions:

-30 °C ~ 60 °C (-22 °F ~ 140
°F)

Humidity 95% or less (non-
condensing)

Power Supply:

12 VDC ± 25%, PoE
(802.3af Class3)

Power Consumption:

12 VDC, 0.7A, max. 8.5W, ?
5.5mm coaxial plug power
PoE (802.3af, 36V to 57V),
0.3 A to 0.1 A, max. 10W

Impact Protection:

IK08 Protection Level

Weather Proof:

IP66

IR Range:

Up to 10m

Dimensions:

?110 mm × 56.4 mm (?4.3" ×

2.2")

Camera: Approx. 400 g (0.9 l

Weight: