

HIKVISION Camara Domo IP 2MP IR Lente Fijo 2.8mm



HIKVISION

Marca: Hikvision

Código del producto: 1893, DS-2CD1121-I

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- 1 / 2.8 "CMOS de exploración progresiva
- 1920 × 1080 @ 30fps
- 2.8MM lente fija
- H.264 +, H.264
- Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON)

Camera

Image Sensor:

1/1.8" Progressive Scan
CMOS

Min. Illumination:

Color: 0.01 Lux @(F1.2,
AGC ON), 0.028 Lux
@(F2.0, AGC ON);
B/W: 0.001 Lux @(F1.2,
AGC ON), 0.0028 Lux
@(F2.0, AGC ON), 0 Lux
with IR

Slow shutter:

Yes

Lens:

2.8 mm

Lens Mount:

M12

Day& Night:

IR Cut Filter

Wide Dynamic Range:

Digital WDR

Digital noise reduction:

3D DNR

Compression Standard

Video Compression:

H.264+/H.264/MJPEG

Video bit rate:

32Kbps~8Mbps

Image

Max. Image Resolution:

1920 x 1080

Sub Stream:

50Hz: 25fps (640 × 480,
640 × 360, 320 × 240)

60Hz: 30fps (640 × 480,
640 × 360, 320 × 240)

Image Enhancement:

BLC, 3D DNR

Image Settings:

Rotate Mode, Saturation,
Brightness, Contrast,
Sharpness adjustable by
client software or web
browser

Day/Night Switch:

Day, Night, Auto,
Scheduled

Network

Alarm Trigger:

Motion detection,
Tampering alarm

Protocols:

TCP/IP, ICMP, HTTP,
HTTPS, FTP, DHCP,
DNS, DDNS, RTP, RTSP,
RTCP, NTP, UPnP™,
SMTP, IGMP, 802.1X,
QoS, IPv6, UDP, Bonjour

General Function:

Anti-flicker, heartbeat,
mirror, password
protection, privacy mask,
watermark

Interface

Communication Interface:

1 RJ45 10M/100M self-
adaptive Ethernet port

General

Operation Condition:	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply:	12 V DC $\pm$ 10%, PoE (802.3at)
Power Consumption:	12 VDC, 0.4 A, max. 5 W; PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, max. 6.5 W
Weather Proof:	IP67

Descripción

- 1 / 2.8 "CMOS de exploración progresiva
- 1920 $\times$ 1080 @ 30fps
- 2.8MM lente fija
- H.264 +, H.264
- Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON)

Camera

Image Sensor:	1/1.8" Progressive Scan CMOS
Min. Illumination:	Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON); B/W: 0.001 Lux @(F1.2, AGC ON), 0.0028 Lux @(F2.0, AGC ON), 0 Lux with IR
Slow shutter:	Yes
Lens:	2.8 mm
Lens Mount:	M12
Day& Night:	IR Cut Filter
Wide Dynamic Range:	Digital WDR
Digital noise reduction:	3D DNR
Compression Standard	
Video Compression:	H.264+/H.264/MJPEG
Video bit rate:	32Kbps~8Mbps

Image

Max. Image Resolution:

1920 x 1080

Sub Stream:

50Hz: 25fps (640 × 480,
640 × 360, 320 × 240)

60Hz: 30fps (640 × 480,
640 × 360, 320 × 240)

Image Enhancement:

BLC, 3D DNR

Image Settings:

Rotate Mode, Saturation,
Brightness, Contrast,
Sharpness adjustable by
client software or web
browser

Day/Night Switch:

Day, Night, Auto,
Scheduled

Network

Alarm Trigger:

Motion detection,
Tampering alarm

Protocols:

TCP/IP, ICMP, HTTP,
HTTPS, FTP, DHCP,
DNS, DDNS, RTP, RTSP,
RTCP, NTP, UPnP™,
SMTP, IGMP, 802.1X,
QoS, IPv6, UDP, Bonjour

General Function:

Anti-flicker, heartbeat,
mirror, password
protection, privacy mask,
watermark

Interface

Communication Interface:

1 RJ45 10M/100M self-
adaptive Ethernet port

General

Operation Condition:

-30 °C to 60 °C (-22 °F to
140 °F), humidity: 95% or
less (non-condensing)

Power Supply:

12 V DC ± 10%, PoE

Power Consumption:

(802.3at)

12 VDC, 0.4 A, max. 5 W;

PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, max.

6.5 W

Weather Proof:

IP67