

HIKVISION Camara Bullet IP 4.0 MP - 30m IR - 3D DNR - POE- IP67



Marca: Hikvision

Código del producto: 1912, DS-2CD1041-I (2.8mm) (O-ST

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- 1/3 "de barrido progresivo CMOS
- Hasta 4.0 megapíxeles
- Lente focal fija de 2,8 mm / 4 mm / 6 mm
- Alcance IR de hasta 30 m.
- Doble flujo WDR digital (rango dinámico amplio)
- 3D DNR (reducción de ruido digital)
- PoE (Power over Ethernet)
- IP67
- Monitorización móvil a través de Hik-Connect
-

Descripción

- 1/3 "de barrido progresivo CMOS
- Hasta 4.0 megapíxeles
- Lente focal fija de 2,8 mm / 4 mm / 6 mm
- Alcance IR de hasta 30 m.

- Doble flujo WDR digital (rango dinámico amplio)
- 3D DNR (reducción de ruido digital)
- PoE (Power over Ethernet)
- IP67
- Monitorización móvil a través de Hik-Connect

Camera

Image Sensor:

1/2.5" Progressive Scan CMOS

Min. Illumination:

Color: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR

Lens:

2.8 mm @F2.0, horizontal field of view 105.8°, 4 mm @F2.0, horizontal field of view 83.6°

6 mm @F2.0, horizontal field of view 55°

Lens Mount:

M12

Day& Night:

IR cut filter with auto switch

Wide Dynamic Range:

Digital WDR

Digital noise reduction:

3D DNR

Compression Standard

Video Compression:

H.264+/H.264/MPEG4/MJPEG

Video bit rate:

32Kbps~16Mbps

Dual Stream:

Yes

Image

Max. Image Resolution:

2688 × 1520

Sub Stream:

50Hz: 25fps @(640 × 360, 352 × 288)

60Hz: 30fps @(640 × 360, 352 × 240)

Image Settings:

Brightness, saturation, contrast, sharpness are adjustable via web browser or client software

BLC:

Support

ROI:	region of interest (support 1 fixed region)
Network	
Network Storage:	NAS (Support NFS,SMB/CIFS)
Protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System Compatibility:	ONVIF (Profile S, Profile G),ISAPI
Interface	
Communication Interface:	1 RJ45 10M/100M self-adaptive Ethernet port
General	
IR Range:	Up to 30 m
Operation Condition:	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply:	12 VDC ± 25%, PoE (802.3af Class3)
Power Consumption:	Max. 5 W/6.5 W (PoE)
Weather Proof:	IP67
Dimensions:	69.1 mm × 66 mm × 172.7 mm (2.7" × 2.6" × 6.8")
Weight:	500 g (1.1 lb.)