

UNIVIEW, 4MP WDR (Motorized)VF 2.8~12 mmt IR Fixed Dome H.265 IK10



Marca:

Código del producto: 1614,
IPC3234SR3-DVZ28

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

Optics

- Day/night functionality
- Smart IR, up to 30m (98 ft) IR distance
- Lowlight surveillance
- 3D DNR (Digital Noise Reduction)

Descripción

Optics

- Day/night functionality
- Smart IR, up to 30m (98 ft) IR distance
- Lowlight surveillance
- 3D DNR (Digital Noise Reduction)

- Características:

IPC3234SR3-DVZ28

Camera	
Sensor	1/3", 4.0 megapixel, progressive scan CMOS
Lens	2.8~12 mm@F1.6
Angle of View (H)	91.0° (wide) ~27.0° (tele)
Zoom/Focus	Motor drive
Shutter	Auto/Manual, 1/6~1/100000 s
Min. Illumination	Colour: 0.02 Lux (F1.6, AGC ON)
	0 Lux with IR
IR Range	Up to 30m (98 ft) IR range
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>55 dB
WDR	Optical WDR (up to 120dB)
Video	
Max. Resolution	2592 × 1520
Video Compression	H.265,H.264,MJPEG
Frame Rate	4MP (2592×1520): Max. 20 fps; 4MP (2560×1440): Max. 25 fps
	3MP (2048×1520): Max. 30 fps; 1080P (1920×1080): Max. 25 fps
Video Streaming	Triple
9:16 Corridor Mode	Supported
ROI	Supported
Evaluative Metering	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
Smart	
Behavior Detection	Intrusion, crossing line, motion detection
Exception Detection	Audio detection
Intelligent Identification	Face detection, Defocus, Scene Change
Statistical Analysis	People counting
Audio	
Audio Compression	G.711
Two-way audio	Supported
Storage	
Edge Storage	Micro SD, up to 128 GB
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP,

Compatible Integration
Interface
Audio I/O

HTTP, HTTPS, SMTP, SIP, 802.1x
ONVIF, API

Audio cable

Input: impedance 35 k Ω ; amplitude 2 V
[p-p]

Output: impedance 600 Ω ; amplitude 2 V
[p-p]

Alarm I/O

1/ 1

Network

1 RJ45 10M/100M Base-TX Ethernet

Video Output

1 BNC, impedance 75 Ω ; amplitude 1 V
[p-p]

Reset Button

Supported

Power Output

DC12V Power Output With PoE

General

Power

12 V DC, or PoE (IEEE802.3 af)

Power consumption: Max.6.6 W (PoE
:Max.7.2 W)

Dimensions ($\varnothing$ x H)

148 x 111.3 mm ($\varnothing$ 5.8" x 4.4")

Weight

0.75 kg (1.7 lb)

Working Environment

-40°C ~ +60°C (-40°F ~ 140°F),
Humidity $\geq$ 95% RH(non-condensing)

Ingress Protection

IP67

Vandal Resistant

IK10