

HIKVISION NVR 32ch 4 SATA



Marca: Hikvision

Código del producto: 1948, DS-7732NI-E4

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a una resolución de hasta 1920 × 1080P
- Hasta 4 interfaces SATA
- Admite la detección de redes, incluido el retardo de red, la pérdida de paquetes, etc.

Descripción

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a una resolución de hasta 1920 × 1080P
- Hasta 4 interfaces SATA
- Admite la detección de redes, incluido el retardo de red, la pérdida de paquetes, etc.

Video/Audio Input

IP video input:

32-ch

Two-way audio input:

1-ch, RCA (2.0 Vp-p, 1k?)

Network

Outgoing bandwidth:

80Mbps

Incoming bandwidth:	160Mbps
Remote connection:	128
Video/Audio Output	
HDMI/VGA output:	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution:	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate:	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output:	1-ch, RCA (Linear, 1k?)
Decoding	
Live view / Playback:	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability:	16-ch@4CIF, 12-ch@720P, 6-ch@1080P
Hard Disk	
SATA:	4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs
Capacity:	Up to 6TB capacity for each HDD
External Interface	
Network Interface:	2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces

Serial Interface:	RS-232; RS-485;
USB Interface:	Front panel: 2 × USB 2.0 Rear panel: 1 × USB 3.0
Alarm In:	16-ch
Alarm Out:	4-ch
General	
Power Supply:	100~240VAC
Consumption(without hard disk and POE):	? 20W
Working Temperature:	-10 °C ~ +55 °C (+14 °F~ +131 °F)
Working Humidity:	10 % ~ 90 %
Chassis:	19-inch rack-mounted 1.5U chassis
Dimensions:	445 × 390 × 70mm (17.5 × 15.3 × 2.8 inch)
Weight(without HDD):	? 4 Kg (8.82 lb)