

HIKVISION NVR 8ch 2 SATA



Marca: Hikvision

Código del producto: 1947, DS-7608NI-E1

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm



Short Description

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a una resolución de hasta 1920 × 1080P
- Hasta 2 interfaces SATA
- Admite la detección de redes, incluido el retardo de red, la pérdida de paquetes, etc.

Descripción

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a una resolución de hasta 1920 × 1080P
- Hasta 2 interfaces SATA
- Admite la detección de redes, incluido el retardo de red, la pérdida de paquetes, etc.

Video/Audio Input

Two-way audio input:

1-ch, RCA (2.0 Vp-p, 1k?)

IP video input:

8-ch

Network

Incoming bandwidth:

80Mbps

Remote connection:	128
Outgoing bandwidth:	80Mbps
Video/Audio Output	
HDMI/VGA output:	1-ch, resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution:	6MP/5MP/3MP/1080P/UX GA/720P/VGA/4CIF/DCI F/2CIF/CIF/QCIF
Frame Rate:	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output:	1-ch, RCA (Linear, 1k?)
Decoding	
Capability:	8-ch@720P, 6-ch@1080P
Live view / Playback:	6MP/5MP/3MP/1080P/UX GA/720P/VGA/4CIF/DCI F/2CIF/CIF/QCIF
Hard Disk	
SATA:	1 SATA interface for 1 HDD
Capacity:	Up to 4TB for each disk
External Interface	
Network Interface:	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
USB Interface:	1 × USB 2.0 and 1 × USB 3.0
Alarm In:	4-ch
Alarm Out:	1-ch

General

Power Supply:	12V DC
Consumption(without hard disk and POE):	? 10W
Working Temperature:	-10 °C ~ +55 °C (+14 °F~ +131 °F)
Working Humidity:	10 % ~ 90 %
Chassis:	2U chassis
Dimensions:	315 × 230 × 45 mm (12.4 × 9.0 × 1.8 inch)
Weight(without HDD):	? 1 kg