

HIKVISION Camara Domo 5 MP EXIR IR 20m IP67 IK10



Marca: Hikvision

Código del producto: 1957, DS-2CE56H0T-VPITF (2.8mm)

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm



Short Description

- CMOS de alto rendimiento de 5 megapíxeles
- Salida analógica HD, hasta 5MP de resolución.
- Lente focal fija de 2,8 mm
- Real día / noche
- Menú OSD, 2D DNR, DWDR
- Tecnología EXIR, hasta 20m de distancia IR.
- IP67, IK10
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)
- Up the Coax (HIKVISION-C)
-

Descripción

- CMOS de alto rendimiento de 5 megapíxeles
- Salida analógica HD, hasta 5MP de resolución.
- Lente focal fija de 2,8 mm
- Real día / noche

- Menú OSD, 2D DNR, DWDR
- Tecnología EXIR, hasta 20m de distancia IR.
- IP67, IK10
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)
- Up the Coax (HIKVISION-C)

Camera

Image Sensor:	5MP CMOS Image Sensor
Effective Pixels:	2560 (H) × 1944 (V)
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens Mount:	M12
Adjustment Range:	Pan: 0° to 355°; Tilt: 0° to 75°; Rotate: 0° to 355°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps; NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization

Menu

D/N Mode:	Auto / Color / B/W
Auto White Balance:	Auto/MWB
BLC:	Support
AGC:	Support
Language:	English/Chinese

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±25%
Impact Protection:	IK10.
Weather Proof:	IP67
IR Range:	Up to 20m
Dimension:	Ø 111 mm × 82.4 mm (Ø 4.4" × 3.2")

Weight:

Approx. 350 g (0.77 lb.)